




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E05B 65/20, 65/19, 47/00	A1	(11) International Publication Number: WO 98/49417 (43) International Publication Date: 5 November 1998 (05.11.98)
<p>(21) International Application Number: PCT/CA98/00400</p> <p>(22) International Filing Date: 29 April 1998 (29.04.98)</p> <p>(30) Priority Data: 2,203,973 29 April 1997 (29.04.97) CA</p> <p>(71) Applicant (for all designated States except US): ATOMA INTERNATIONAL INC. [CA/CA]; 521 Newpark Boulevard, Newmarket, Ontario L3Y 4X7 (CA).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): TOMASZEWSKI, Kris [CA/CA]; 24 Fieldview Crescent, Markham, Ontario L3R 3H7 (CA). BANIAK, Grzegorz, H. [CA/CA]; 2 Chelsea Drive, Etobicoke, Ontario M8W 4R6 (CA). JORGENSEN, Gregory, A. [US/US]; 27 Dennison Road, Oxford, MI 48371 (US).</p> <p>(74) Agent: IMAI, Jeffrey, T.; Magna International Inc., 337 Magna Drive, Aurora, Ontario L4G 7K1 (CA).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	

(54) Title: CONTROL ASSEMBLY FOR LIFT GATE OR SLIDING AND CARGO DOORS



(57) Abstract

A control assembly for releasing a latch has a base plate (26) for mounting components of the control assembly. A pivotally mounted (28) input lever is movable between a ready position and a release position. The input lever (28) connects to a release handle (22). A pivotally mounted output lever (30) connects to a latch (14, 16) and transmits a releasing force. A pivotally mounted locking lever (34) is rotatable between a locked position and an unlocked position. A link (98) slidably engages the output lever (30) and pivotally engages the locking lever (34). When the locking lever (34) moves between the locked and unlocked positions, the link (98) responsively decouples and couples the input lever (28) and the output lever (30) to allow independent and dependent rotation thereof, respectively, selectively transferring the releasing force from the release handle (22) to the latch (14, 16).

-2-

position, then the input arm of the input lever will not be able to access the floating pin, and hence the output lever will not operate in spite of the fact that the input lever will operate. Such a control assembly therefore includes a first pivot connected to the locking lever, a second pivot connected with the floating pin, a third pivot about which the locking lever
5 pivots, and a fourth pivot about which the input lever and the output lever pivot. Within the actuator itself, it is estimated that the electrical requirements would be approximately 10 watts normally, and peak at approximately 50 watts or more, with up to 5 amps being drawn by the motor.

10 Clearly therefore, the problems can be seen in providing such a device in that a significant amount of the power utilized by the actuator goes into friction losses when transferring the power from the actuator to the actual cables. Secondly, the reliability of the product must be questioned in that many of the parts, for example such as the tab from the locking lever which accesses the opening of the linear actuator plunger, undergoes a
15 dynamic load over each cycle and may tend to fail in time. Secondly, the pivot for the locking lever may tend to bind in time, or the floating pin may also bind within the slot between its two positions.

Summary of the Invention

20 The disadvantages of the prior art may be overcome by providing a latch control assembly having a simple mechanism for locking and unlocking a lift gate or door and for effecting unlatching thereof.

According to one aspect of the invention, there is provided a control assembly for
25 releasing a latch. The control assembly has a base plate for mounting components of the control assembly. A pivotally mounted input lever is movable between a ready position and a release position. The input lever connects to a release handle. A pivotally mounted output lever connects to a latch and transmits a releasing force. A pivotally mounted locking lever is rotatable between a locked position and an unlocked position. A link
30 slidably engages the output lever and pivotally engages the locking lever. When the locking lever moves between the locked and unlocked positions, the link responsively decouples and couples the input lever and the output lever to allow independent and

dependent rotation thereof, respectively, selectively transferring the releasing force from the release handle to the latch.

Description of the Drawings

- 5 In drawings which illustrate an embodiment of the invention,
Figure 1 is a perspective view of lift gate incorporating the control assembly
 of the present invention;
Figure 2 is an exploded view of the control assembly of the present invention;
 and
10 Figure 3 is a perspective view of the control assembly of Figure 2;

Description of the Invention

Referring now to Figure 1, there is illustrated a tailgate assembly or door assembly
15 12, normally pivotally mounted, which allows the door 12 to swing upwardly in the
conventional motion of a tailgate. Two latches, 14 and 16 are conveniently located
proximate the sides of the tailgate 12 which will engage keepers or strikers when the
tailgate 12 is closed. The latches 14, 16 are oriented in such a way that the fish mouths will
engage with the respective strikers as is well known in the art. The latches 14, 16 are
20 conventional and include pawl release levers to which are connected the Bowden cables 18,
20 for each latch. The Bowden cables 18, 20 are conveniently run through clips in openings
in the body panels which allow motion of the cable and yet securement of the cable in
relation to the panel. The Bowden cables 18, 20 operatively connect to the control
assembly 10 of the present invention. Release handle 22 is operatively connected via a
25 cable or rod 24 to the input lever of control assembly 10. Release handle 22 is pivotally
mounted to the tailgate 12 in a manner conventional in the art. Actuation of the release
handle 22 effects the release of the latches 14, 16 when the control assembly 10 is in the
operative or unlocked position which will be described hereinafter.

30 Referring now to Figure 2, there is illustrated the control assembly 10 which
includes a mounting or base plate 26, an input lever 28, an output lever 30, a locking block
32, a locking lever 34 and an actuator 36.

Base plate 26 is preferably a stamped metal formed with various features including mounting holes, Bowden cable attachment tabs 38, 40, an arcuate guide slot 42, and a control window 44. Tabs 38, 40 extend generally perpendicular from base plate 26. Tabs 38
5 and 40 have cutouts for receiving the outer cable shell or sheath of Bowden cables 18, 20. Base plate 26 has an embossed area 46 having a bore 48 and an embossed area 50 having a bore 52. Base plate 26 is otherwise configured for mounting the components of the control assembly 10 onto the base plate 26 and for matching the footprint for mounting the control assembly 10 onto the frame of the lift gate 12.

10

Input lever 28 is preferably a stamped metal and formed to be pivotally mounted onto base plate 26. Input lever 28 has two arms 54, 56 extending from opposite sides of pivot 58. Arm 54 has tabs 60, 62 extending in opposite directions. Tab 62 extends towards the base plate 26 and extends through control window 44. Control window 44 limits the
15 pivotal travel of the input lever 28 between a ready position and a release position. Arm 56 has a tab 64 having an aperture for receiving spring 66. Spring 66 extends between tab 40 and tab 64 to bias the input lever 28 to the ready position.

Output lever 30 is preferably a stamped metal and formed to be pivotally mounted
20 onto base plate 26 coaxially with input lever 28. Output lever 30 is mounted on pivot pin 68 which pivotally mounts input lever 28 through bore 48 on base plate 26. Output lever 30 has three arms 70, 72 and 74. Arms 70, 72, 74 extend radially from a central pivot 76 through which pivot pin 68 extends. Arms 70, 72 are preferably diametrically opposed. The distal ends of arms 70, 72 has a bore for receiving clips 78, 80 in a snap fit. Clips 78
25 and 80 are connected to the ends of cables 18, 20, respectively. Pivotal movement of output lever 30 will simultaneously extend and retract each of cables 18, 20 for release of latches 14, 16. Arm 72 has a tab 82 at the distal end, which tab extends through guide slot 42 on base plate 26. Guide slot 42 limits pivotal travel of the output lever 30. Arm 74 has a radially extending slot 84 and a cooperating axially extending flange 86. Spring 87 extends
30 between arm 74 and the base plate 26 to bias the output lever 30 to a position, wherein the cables 18, 20 will be at an unextended length or retracted position.

The locking lever 34 is preferably a stamped metal component and formed to be drivingly mounted on output shaft 88 of actuator 36. Locking lever has two arms 90, 92 extending from a central core 94. Core 94 has an aperture complementary to the shape of output shaft 88 for a driving engagement therewith. A screw 95 attaches the locking lever 34 to the output shaft 88. Arm 90 has a tab 96 at the distal end. Arm 92 has a keyway aperture 97 for pivotally connecting link 98 of locking block 32. Connecting link 98 has, at one end, pin 100 having locking tabs 102 and locking block 32 at the opposite end. Locking block 32 is pivotally connected to and slightly spaced from the connecting link 98. The locking tabs 102 can be inserted into keyway aperture 97 to pivotally connect the connecting link 98 to the locking lever 34. The locking block 32 engages the output lever 30. Specifically the mounting pin of the locking block 32 will be inserted through slot 84 of output lever 30. Locking block 32 will slide against flange 86. Rotation of locking lever 34 will cause the locking block 32 to slide in the slot 84 between an operative or unlocked position wherein the locking block 32 will extend between the flange 86 and the tab 60 of input lever 28 and an inoperative or locked position wherein the locking block 32 does not engage tab 60 of input lever 28. In the embodiment illustrated, the operative position is radially outward and the inoperative or locked position is radially inward along slot 84.

Actuator 36 is conventional in design. In one embodiment of the invention, a motor drives output shaft 88 through a series of gears (not illustrated) to rotate locking lever 34 between a locked position and an unlocked position.

Referring now to Figure 3, the locking block 32 moves linearly along the slot 84. When the locking block 32 is in the operative or unlocked position, movement of the input lever 28 will translate to the output lever 30 through the locking block 32, so that the input lever 28 is coupled to the output lever 30 to rotate dependently. However, when the locking block 32 travels radially inwardly to the disengaged or locked position, the operative connection between the input lever 28 and the output lever 30 is removed. Input lever 28 is uncoupled from the output lever 30 to rotate independently. Should the handle 22 be utilized and the input lever 28 rotated, the input lever 28 will merely freely move on its pivot without moving any of the other components of the control assembly 10. Further, the locking lever 34 has an emergency manual override tab 96 which may be accessed should

the actuator 36 fail, or alternatively in another embodiment, when the actuator is not present, be in communication with a manually operable user accessible device such as a knob or the like or alternatively in communication with a child proofing lever.

5 In operation therefore, the actuator 26 or user accessible operator would be operated or powered via a push button, knob, a remote or the like causing the rotation of the locking lever 34 about its pivot, and therefore cause the linear motion of the locking block 32 relative to arm 74 of the output lever 30, moving the locking block 32 in and out of operative interconnection between the input lever 28 and the output lever 30 to couple and
10 uncouple the input lever 28 and the output lever 30. Therefore, when the locking block 32 is in the operative or unlocked position, the actuating tab 60 of the input lever 28 will engage the locking block 32 adjacent thereto which in turn will transmit any force transmitted through the input lever 28 to the flange 86 of the output lever 30 causing the output lever 30 to rotate upon its pivot to allow for the release of the latches 14, 16 as the
15 cables 18, 20 are retracted responsive to the output lever 30 rotation. However, when the locking block 32 is translated to the disengaged or locked position, whereat the tab 60 can no longer engage the locking block 32, regardless of movement of the handle 22 and input lever 28, the latches 14, 16 cannot release.

20 The invention has been described in an illustrative manner with respect to the preferred embodiments thereof, and it is understood and implied that the terminology that has been used is intended to be for descriptive purposes only and not for the interpretation in limiting the invention. As many changes can be made to the preferred embodiments of the invention without departing from the scope thereof; it is intended that all matter
25 contained herein be considered illustrative of the invention and not in a limiting sense.

We claim:

1. A control assembly for releasing a latch, said control assembly comprising
a base plate for mounting components of the control assembly,
a pivotally mounted input lever movable between a ready position and a release
5 position, the input lever constructed and arranged to be connected to a release handle,
a pivotally mounted output lever constructed and arranged to be connected to a latch
and to transmit a releasing force therethrough,
a pivotally mounted locking lever rotatable between a locked position and an
unlocked position,
10 a link slidably engaging said output lever and pivotally engaging said locking lever,
wherein when said locking lever moves between the locked and unlocked positions, the link
responsively decouples and couples the input lever and the output lever to allow
independent and dependent rotation thereof, respectively, selectively transferring the
releasing force from the release handle to the latch.
- 15 2. A control assembly as claimed in claim 1 wherein said input lever and said output
lever are commonly mounted.
3. A control assembly as claimed in claim 2 wherein said output lever has a radially
extending slot for slidable receiving said link.
4. A control assembly as claimed in claim 3 wherein said link has a locking block in
20 sliding engagement with the output lever, said locking block juxtaposes a flange on the
output lever and a tab on the input lever when the input lever and the output lever are
coupled together and disengages from at least one of the flange and the tab when the input
lever and the output lever are uncoupled.
5. A control assembly as claimed in claim 1 wherein said output lever has a radially
25 extending arm constructed and arranged to receive a bowden cable operatively connected to
the latch and said base plate has a bracket for retaining a sheath of the bowden cable.
6. A control assembly as claimed in claim 5 wherein said output lever has a second
radially extending arm having a slot for slidable receiving said link.
7. A control assembly as claimed in claim 6 wherein said link has a locking block in
30 sliding engagement with the output lever, said locking block juxtaposes a flange on the
output lever and a tab on the input lever when the input lever and the output lever are

coupled together and disengages from at least one of the flange and the tab when the input lever and the output lever are uncoupled.

8. A control assembly as claimed in claim 7 wherein said input lever and said output lever are commonly mounted.

5 9. A control assembly as claimed in claim 1 wherein said control assembly further comprises an actuator and the locking lever is mounted on said actuator for drivingly effecting said pivotal movement.

10. A control assembly as claimed in claim 9 wherein said output lever has a radially extending arm constructed and arranged to receive a bowden cable operatively connected to
10 the latch and said base plate has a bracket for retaining a sheath of the bowden cable.

11. A control assembly as claimed in claim 10 wherein said output lever has a second radially extending arm having a slot for slidable receiving said link.

12. A control assembly as claimed in claim 11 wherein said link has a locking block in sliding engagement with the output lever, said locking block juxtaposes a flange on the
15 output lever and a tab on the input lever when the input lever and the output lever are coupled together and disengages from at least one of the flange and the tab when the input lever and the output lever are uncoupled.

13. A control assembly as claimed in claim 12 wherein said input lever and said output lever are commonly mounted.

20 14. A control assembly as claimed in claim 13 wherein said locking lever is constructed and arranged to be manually operated.

15. A control assembly as claimed in claim 9 wherein said control assembly simultaneously effects release of at least two latches.

16. A control assembly as claimed in claim 15 wherein said output lever has a plurality
25 of radially extending arms, at least two of said arms constructed and arranged to receive a bowden cable operatively connected to each of said at least two latches and said base plate has a bracket for retaining a sheath of each of said bowden cables.

17. A control assembly as claimed in claim 10 wherein one of said arms has a slot for slidable receiving said link.


30 18. A control assembly as claimed in claim 17 wherein said link has a locking block in sliding engagement with the slot, said locking block juxtaposes a flange on the output lever and a tab on the input lever when the input lever and the output lever are coupled together


and disengages from at least one of the flange and the tab when the input lever and the output lever are uncoupled.

19. A control assembly as claimed in claim 18 wherein said input lever and said output lever are commonly mounted.

- 5 20. A control assembly as claimed in claim 19 wherein said locking lever is constructed and arranged to be manually operated.

FIG. 1.








FIG. 3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 98/00400

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 E05B65/20 E05B65/19 E05B47/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 E05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 295 643 A (MITSUI KINZOKU KOGYO KABUSHIKI KAISHA) 5 June 1996 see page 14, paragraph 2 - page 15, paragraph 2; figures 5, 11-13 ---	1-20
X	US 3 563 589 A (KWASIBORSKI) 16 February 1971 see the whole document ---	1-4
X	US 4 334 704 A (YAMADA SHINJIRO) 15 June 1982 see the whole document ---	1-4
A	DE 39 23 726 A (BAYERISCHE MOTOREN WERKE AG) 24 January 1991 see figure 1 --- -/--	1, 5, 10

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

16 September 1998

Date of mailing of the international search report

24/09/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Westin, K

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 98/00400

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 43 12 344 A (MERCEDES BENZ AKTIENGESELLSCHAFT) 21 July 1994 see abstract; figure 1 ---	1, 15
A	DE 39 02 873 A (KIEKERT GMBH & CO KG) 15 February 1990 see figure 8 ---	1-4, 9
A	DE 44 40 839 A (AISIN SEIKI K.K.) 18 May 1995 see figures 4-6, 10-12 ---	1-4
P, X	EP 0 826 855 A (MANNESMANN VDO AG) 4 March 1998 see the whole document ---	1-4, 9
P, X	EP 0 775 791 A (ROCKWELL LIGHT VEHICLE SYSTEMS) 28 May 1997 see the whole document -----	1-4, 9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CA 98/00400

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2295643 A	05-06-1996	JP 6294245 A	21-10-1994
		JP 6307141 A	01-11-1994
		JP 2739673 B	15-04-1998
		JP 7034743 A	03-02-1995
		GB 2295642 A,B	05-06-1996
		GB 2276913 A,B	12-10-1994
		US 5618068 A	08-04-1997
		KR 9707102 B	02-05-1997
US 3563589 A	16-02-1971	NONE	
US 4334704 A	15-06-1982	NONE	
DE 3923726 A	24-01-1991	NONE	
DE 4312344 A	21-07-1994	NONE	
DE 3902873 A	15-02-1990	DE 8915994 U	05-11-1992
		FR 2636364 A	16-03-1990
		GB 2222203 A,B	28-02-1990
		US 4978154 A	18-12-1990
DE 4440839 A	18-05-1995	JP 7139237 A	30-05-1995
		JP 7139238 A	30-05-1995
		JP 7139239 A	30-05-1995
		GB 2284853 A,B	21-06-1995
EP 826855 A	04-03-1998	DE 19635414 A	05-03-1998
EP 775791 A	28-05-1997	GB 2307507 A	28-05-1997
		WO 9720121 A	05-06-1997